

# SEAMLESS POWER FOR **UNSTOPPABLE DREAMS**



**LEYPower DIESEL GENERATORS 15 kVA TO 250 kVA**

Powered by Reliable, Rugged & Robust engines | Best-in-class fluid efficiency | Longest oil change interval

# NEW AGE POWER. AGE OLD TRUST

Power your business with the state-of-the-art Diesel Gensets from Ashok Leyland

DG MODEL	Unit	LP 15	LP 25	LP 30	LP 35/40	LP 45	LP 60	LP 75/82.5	LP 100	LP 125	LP 160	LP 180	LP 250
Power rating*	kVA	15	25	30	35/40	45	60	75/82.5	100	125	160	180	250
Electric power	kWe	12	20	24	28/32	36	48	60/66	80	100	128	144	200
Rated current	A	21	35	42	49/56	63	84	104/115	139	174	223	250	346
DG size L X W	mm x mm	1750 X 1000	2000 X 1000	2000 X 1000	2500 X 1200	2500 X 1200	2700 X 1200	2850 X 1300	2850 X 1300	3100 X 1300	3500 X 1400	3500 X 1400	4700 X 1600
Height (including base)	mm	1200	1350	1350	1450	1450	1510	1510	1610	1610	1850	1850	2020
DG weight approx.	kg	676	750	750	1090	1100	1380	1417	1900	2050	2210	2280	4500
Fuel tank capacity	L	55	60	60	140	140	140	190	200	200	250	250	340
Battery capacity	Ah	90	90	90	90	90	90	90	90	90	110	110	110
System DC voltage	V	12	12	12	12	12	12	12	12	12	12	12	24
<b>Engine model</b>		<b>H2G4DM15</b>	<b>P15G4DE25</b>	<b>P15G4DE30</b>	<b>H4G4DE40</b>	<b>H4G4DE45</b>	<b>H4G4DE60</b>	<b>H4G4DE82</b>	<b>H4G4DE100</b>	<b>H6G4DE125</b>	<b>H6G4DE160</b>	<b>H6G4DE180</b>	<b>A6G4DE250</b>
Engine rated	kW/ hp	14.6/ 19.5	25/ 33.3	28/ 37	39/ 52	42.5/ 56.5	54/ 72	78/ 104	92/ 122	116/ 154	147/ 197	165/ 220	223/ 303
Aspiration		NA	TCIC	TCIC	TCIC	TCIC	TCIC	TCIC	TCIC	TCIC	TCIC	TCIC	TCIC
No. of cylinders & configuration		2, Inline	3, Inline	3, Inline	4, Inline	4, Inline	4, Inline	4, Inline	4, Inline	6, Inline	6, Inline	6, Inline	6, Inline
Bore x Stroke	mm x mm	104 X 118	80 X 98	80 X 98	104 X 113	104 X 113	104 X 113	104 X 118	104 X 118	104 X 118	104 X 118	104 X 118	112 X 135
Displacement	L	2	1.5	1.5	3.84	3.84	3.84	4	4	6	6	6	7.98
Compression ratio		16.5 ± 0.5 : 1	16.5 ± 0.5 : 1	16.5 ± 0.5 : 1	16.5 ± 0.5 : 1	16.5 ± 0.5 : 1	16.5 ± 0.5 : 1	16.5 ± 0.5 : 1	16.5 ± 0.5 : 1	16.5 ± 0.5 : 1	16.5 ± 0.5 : 1	16.5 ± 0.5 : 1	17.5 ± 0.5 : 1
Lube oil capacity approx.	L	6	4.5	4.5	8.5	8.5	8.5	12	12	18	18	18	28
Coolant capacity approx.	L	10	11	11	14	14	16	18	20	22	24	24	55
Governing class		A1	A0	A0	A0	A0	A0	A0	A0	A0	A0	A0	A0
Governer used		Mechanical	Electronic	Electronic	Electronic	Electronic	Electronic	Electronic	Electronic	Electronic	Electronic	Electronic	Electronic
Oil change period		600 hrs or 1 year	500 hrs or 1 year				750 hrs or 1 year						
Lube oil specification		Gulf Leypower XLE											
Generator controller		GC 902				GC 1206							

Ashok Leyland, a trusted brand in power solutions, is now geared up to power your business sustainably with the all new CPCB IV+ Diesel Gensets ranging from 15 kVA to 250 kVA.

These elegantly designed, silent Diesel Gensets meet the most rigorous emission norms and are available through our extensive network across India.

Ashok Leyland provides comprehensive Powergen solutions, encompassing Genset transportation, loading/unloading, positioning, and installation, covering, earthing, cabling, exhaust piping, room treatment, and obtaining approvals from relevant authorities.

We, at Ashok Leyland, take pride in having powered over 300,000 diesel generators in the last decade for diverse applications such as infrastructure, retail chains, rental, banks, hospitals, petroleum retail outlets, industries, hotels & resorts, educational institutions and others.



Single POC for engine, alternator, panel and installation



Max functionality at lower operating costs



Silent operations



Extended oil change interval



Bold and vibrant design



Compact size

\* Power Rating- As per BS 5514/ ISO 3046/ ISO 8528 under standard reference conditions.

ENGINE

IOT & TELEMATICS

SERVICE



An ISO 9001: 2008 Certified Company

Unit - 1 : 9/A, Shyam Ujwal Industrial Estate, Opp. State Bank of India, Phase-I, GIDC, Vatava, Ahmedabad-382445, Gujarat, India.

Unit - 2 : 31/A Sakriba Estate, B/h. Indo-Geman Tool Room, Phase-IV, GIDC - Vatva, Ahmedabad-382445. Gujarat - India.

M : +91 - 98250 35828 | 85111 60695  
 E-mail : [info@ramptechnomation.com](mailto:info@ramptechnomation.com)  
[dgset@ramptechnomation.com](mailto:dgset@ramptechnomation.com)  
 Website : [www.ramptechnomation.com](http://www.ramptechnomation.com)

## RAMP TECHNOMATION PRIVATE LIMITED

**AUTHORISED DEALER**

